

Making code. Using GCC tool chain

```
make -f __auto.mak -j 1
```

```
set -e; avr-gcc -MM -mmcu=atmega8 -I. -std=gnu99 -Os -gstabs -Wa,-adhlns=gt-jtx.lst
```

```
-funsigned-char -funsigned-bitfields -fpack-struct -fshort-enums -Wall -Wstrict-prototypes  
gt-jtx.c \
```

```
| sed 's,\(.*\)\\.o[ :]*,\\1.o \\1.d : ,g' > gt-jtx.d; \
```

```
[ -s gt-jtx.d ] || rm -f gt-jtx.d
```

```
sed: invalid option -- s
```

```
Usage: sed [OPTION]... {script-only-if-no-other-script} [input-file]...
```

```
-n, --quiet, --silent
```

```
suppress automatic printing of pattern space
```

```
-e script, --expression=script
```

```
add the script to the commands to be executed
```

```
-f script-file, --file=script-file
```

```
add the contents of script-file to the commands to be executed
```

```
-c --nocr turn off \r$ translation; must be first switch on command line
```

```
--help display this help and exit
```

```
-V, --version output version information and exit
```

If no -e, --expression, -f, or --file option is given, then the first non-option argument is taken as the sed script to interpret. All remaining arguments are names of input files; if no input files are specified, then the standard input is read.

E-mail bug reports to: [bug-gnu-utils@gnu.org](mailto:bug-gnu-utils@gnu.org) .

Be sure to include the word ``sed'' somewhere in the ``Subject:'' field.

```
set -e; avr-gcc -MM -mmcu=atmega8 -I. -std=gnu99 -Os -gstabs -Wa,-adhlns=lcd.lst
```

```
-funsigned-char -funsigned-bitfields -fpack-struct -fshort-enums -Wall -Wstrict-prototypes  
lcd.c \
```

```
| sed 's,\(.*\)\\.o[ :]*,\\1.o \\1.d : ,g' > lcd.d; \
```

```
[ -s lcd.d ] || rm -f lcd.d
```

```
sed: invalid option -- s
```

```
Usage: sed [OPTION]... {script-only-if-no-other-script} [input-file]...
```

```
-n, --quiet, --silent
```

```
suppress automatic printing of pattern space
```

```
-e script, --expression=script
```

```
add the script to the commands to be executed
```

```
-f script-file, --file=script-file
```

```
add the contents of script-file to the commands to be executed
```

```
-c --nocr turn off \r$ translation; must be first switch on command line
```

```
--help display this help and exit
```

```
-V, --version output version information and exit
```

If no -e, --expression, -f, or --file option is given, then the first non-option argument is taken as the sed script to interpret. All remaining arguments are names of input files; if no input files are specified, then the standard input is read.